

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: 30 wt. NON-DETERGENT OIL

Model Number: APC01Q

Chemical Name: Non-Detergent Motor Oil

Chemical Family: Blend

Manufacturer: General Air Products, Inc.

604 Jeffers Circle

Exton, PA 19341

Emergency Telephone Numbers:

Information: 800-345-8207 8am-5pm EST M-F

CHEMTREC: 800-424-9300 24 hrs everyday

2. COMPOSITION / INFORMATION ON INGREDIENTS

EXPOSURE GUIDELINES	OSHA	ACGIH	UNIT
Component / CAS Number	LO% HI%	TWA STEL TWA STEL	MG / M3
LIMITS FOR THE PRODUCT	5	5	
ADDITIVE MIXTURE CONTAINING COMPOUNDS OF CA, ZN, S, AND P	1.00%		
DEFOAMER	50 PPM		
ORGANIC ZINC COMPOUND(S) MEASURED AS ZN			
7440-66-6	.006%		
SOLVENT-DEWAXED RESIDUAL OIL (PETROLEUM)			
64740-62-7	0 TO 34%		
SOLVENT-DEWAXED HEAVY PARAFFINIC DISTILLATE (PETROLEUM)			
64742-65-0	65 TO 99%		
ADDITIONAL EXPOSURE LIMITS	----- GOVERNMENT REGULATION		
OTHER LIMIT - OIL MIST: 5MG/M3	OSHA PEL / ACGHI TLV		

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW

MAY CAUSE SKIN IRRITATION

APPEARANCE: AMBER FLUID

ODOR: LUBE OIL ODOR

POTENTIAL HEALTH EFFECTS:

INHALATION: NO EFFECTS EXPECTED.

INGESTION: PRACTICALLY NON-TOXIC

EYE CONTACT: EXPECTED TO BE MINOR EYE IRRITANT.

SKIN CONTACT: PRACTICALLY NON-TOXIC IF ABSORBED (LD50 > 2000 MG/KG). MAY CAUSE MODERATE IRRITATION WITH PROLONGED OR REPEATED CONTACT

CARCINOGEN LISTED BY: IARC(NO) NTP(NO) OSHA(NO) ACGIH(NO) OTHER(NO)

NFPA / HMIS CLASSIFICATION

HEALTH - 0/0

FLAMMABILITY - 1/1

REACTIVITY - 0/0

HAZARD RATING

0 = LEAST 1 = SLIGHT

2 = MODERATE 3 = HIGH

4 = EXTREME

(NA = Not Applicable ND = No Data NE = Not Established)

4.FIRST AID MEASURES

INHALATION: Move to fresh air.

EYE CONTACT: Flush with water for at least 15 minutes. If irritation persists obtain medical assistance.

SKIN CONTACT: Wash with soap and water until no odor remains. If redness or swelling develops obtain medical assistance. Wash clothing before reuse.

INGESTION: If large amounts of this material are ingested, give quantities of water, induce vomiting, and promptly obtain medical attention

5.FIRE FIGHTING MEASURES

FLASHPOINT (METHOD): 445°F Minimum COC; 201°C Minimum COC

FLAMMABLE LIMITS: Not established

AUTOIGNITION TEMP: 775°F Estimated; 359°C Estimated

EXTINGUISHING MEDIA: Water spray, dry chemical, carbon dioxide (CO₂), foam.

FIRE FIGHTING INSTRUCTIONS: Avoid breathing smoke and vapor.

FIRE FIGHTING EQUIPMENT: Wear self-contained breathing apparatus and protective clothing. Use water spray to keep fire-exposed containers cool

HAZARDOUS COMBUSTION PRODUCTS: Normal combustion forms carbon dioxide and water vapor; incomplete combustion can produce carbon monoxide.

6.ACCIDENTAL RELEASE MEASURES

SPILLS OR LEAKS: Contain spill, advise EPA; state agency if required. Absorb on inert material, shovel, sweep or vacuum spill.

7.HANDLING AND STORAGE

NFPA Class IIIB Storage. Wash thoroughly after handling

8.EXPOSURE CONTROLS / PERSONAL PROTECTION

VENTILATION: Ventilate as needed to comply with exposure limit. General dilution ventilation acceptable.

PERSONAL PROTECTIVE EQUIPMENT

EYE: Splash proof chemical goggles recommended to protect against splash of product.

GLOVES: Protective gloves recommended when prolonged skin contact cannot be avoided. The following glove materials are acceptable: polyvinyl chloride (PVC); neoprene; nitrile; polyvinyl alcohol; viton.

RESPIRATOR: None is needed under normal conditions with adequate ventilation. If exposure exceeds the control limits, respiratory protective equipment which meets 29 CFR 1910.134 and is NIOSH/MSHA approved must be worn.

OTHER: If contact is unavoidable, wear chemical resistant clothing. The following materials are acceptable as protective clothing materials: polyvinyl alcohol (PVA); polyvinyl chloride (PVC); neoprene; nitrile; viton; polyurethane; launder soiled clothes.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/ODOR: AMBER FLUID/SLIGHT ODOR

VAPOR PRESSURE: <0.0001 (MM HG @ 20°C)

MOLECULAR WEIGHT: N/A (G/MOLE)

SOLUBILITY IN WATER: NIL (% BY VOLUME)

EVAPORATION RATE: 1000X SLOWER (ETHYL ETHER = 1)

SPECIFIC GRAVITY: 0.86 (WATER=1)

VISCOSITY: 150 SUS @ 100°F

BOILING POINT: HIGH

MELTING POINT: N/A

PACKING DENSITY: N/A

OCTANOL/WATER COEFF: ND

ODOR THRESHOLD: ND

VAPOR DENSITY: 10+ (AIR = 1)

32CST @ 40°C

10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID: None known

MATERIALS TO AVOID: Strong oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur

HAZARDOUS DECOMPOSITION: Combustion will produce carbon monoxide and asphyxiants.

11. TOXICOLOGICAL INFORMATION

FOR THE PRODUCT

INHALATION: Low acute toxicity **SKIN:** Practically non-toxic if absorbed. Mild irritation with prolonged or repeated contact. **EYE:** Mildly irritating on contact. **ORAL:** Small amounts practically non-toxic; acute toxicity: estimated oral LD50 in rats is: > 15 g/kg estimated draize skin irritation score is ; 2.10 out of 8.0

SEVERELY SOLVENT REFINED HEAVY PARAFFINIC PETROLIUM OIL: **INHALATION:** low acute toxicity **SKIN:** practically non-toxic if absorbed, may cause moderate irritation with prolonged and repeated contact

EYE: minimally irritating on contact. **INGESTION:** Practically non-toxic if swallowed

CALCIUM SULFONATE: **INHALATION/INGESTION:** No data available. **SKIN:** Moderate irritant
Caused allergic skin reaction in animals. **EYE:** Moderate to severe irritation

BUTYLATED PHENOL: No data available for all routes of exposure.

ZINC DIALKLY DITHIOPHOSPHATE: **INHALATION:** Toxic hydrogen sulfide is generated when heated above 200 deg. F. This can cause central nervous system (brain) effects, nausea, dizziness, confusion, loss of sense of smell, muscle cramps, in coordination, unconsciousness, coma, respiratory failure, or death. **SKIN:**

Prolonged or repeated contact may cause moderate irritation, redness, drying, cracking, dermatitis. **EYE:** Irritant

ORAL: Harmful if swallowed.

ACRYLIC COPOLYMER: No data available for all routes of exposure.

2-ETHYLHEXANOL: **INHALATION:** Overexposure may cause nose, throat, irritation, nasal discomfort and discharge, chest pain, cough, headache, nausea, vomiting. **SKIN:** irritant. May cause corneal injury.

ORAL: Moderately toxic. May cause abdominal discomfort, nausea, vomiting and diarrhea.

12. ECOLOGICAL INFORMATION

ECOTOXICITY: No data available.

13. DISPOSAL INFORMATION

Follow federal, state, and local regulations. Not RCRA hazardous waste if uncontaminated. If "used" RCRA or teria (ignitability, reactivity, corrosivity, toxicity characteristics) must be determined. Do not flush to drain / storm sewer. Contract to authorized disposal service.

14. TRANSPORTATION INFORMATION

DOT
PROPER SHIPPING NAME: Petroleum Lubricating Oil
HAZARD CLASS: Not regulated
ID NUMBER: Not regulated
LABEL REQUIRED: Not regulated
IMDG PROPER SHIPPING NAME: ND
IATA PROPER SHIPPING NAME : ND

15. REGULATORY INFORMATION

TSCA: This material is in compliance with the TOXIC SUBSTANCES CONTROL ACT (15 USC 2601-2629) and is listed in the TSCA Inventory.

SARA 302 THRESHOLD PLANNING QUANTITY,	N/A	
SARA 304 REPORTABLE QUANTITY,	N/A	
SARA 311 / 312 REPORTING,	Health	Immediate (Acute) No
	Health	Delayed (Chronic) No
	Physical Fire	No
	Physical Sudden Release of Pressure	No
	Physical Reactive	No

When a product and/or component is listed below, the regulatory list on which it appears is indicated.

ZINC DIALKYL DITHIOPHOSPHATE - NJ 01

01 = SARA 313	02 = SARA 302/304	03 = IARC CARCINOGEN
04 = OSHA CARCINOGEN	05 = ACGIH CARCINOGEN	06 = NTP CARCINOGEN
07 = CERCLA 302.4	08 = WHMIS CONTROLLED PROD.	
10 = OTHER CARCINOGEN		
PA = PA RTK	NJ = NEW JERSEY RTK	CA = CALIFORNIA PROP 65
MA = MASS. RTK	MI = MICHIGAN 406	MN = MINNESOTA RTK
FL = FLORIDA	RI = RHODE ISLAND	IL = ILLINOIS
NY = NEW YORK	WV = WEST VIRGINIA	CT = CONNECTICUT
LA = LOUISIANA	ME = MAINE	OH = OHIO

16. OTHER INFORMATION

GENERAL AIR PRODUCTS, INC.
604 JEFFERS CIRCLE
EXTON, PA 19026
1-800-345-8207

The information on this form is furnished solely for the purpose of compliance with the OSHA Act, and shall not be used for any other purpose. The information herein is given in good faith and is based on data considered accurate. However, no warranty, expressed or implied, is made regarding the accuracy of this data or the results to be obtained from the use thereof.