
Open Complete Residential Fire Protection Pump System





NOTE: Use page 2 of this document to select the correct model number based on your systems' pressure and flow requirements.

*Standard RFP System Voltage is 230/1/60. For other voltage requirements, consult factory.

All information subject to change without notice.

General Air Products' Residential Fire Protection Pump System (RFP System) is the benchmark of quality for meeting 2010 NFPA 13D application requirements.

Our complete RFP Systems deliver a wide variety of features and benefits that work together to meet the need of your application simply, efficiently and reliably.

- True Stainless Steel Pump
- Non-Ferrous Piping System
- NEMA Rated Electrical Control Box
- Power "On" Indicator
- Audible Alarm System
- Alarm Signal Contact
- Motor Starter "Reset"
- H-O-A Switch (allows pump test)
- Motor Overload Protection
- "Water Flow" Alarm Indicator
- Adjustable Pressure Switch
- DPDT Flow Switch
- Water Delivery Pressure Gauge
- Return Connection

- See Brochure for Complete Feature List

Model Number	AMP Draw*	Weight (lbs.)
OPS11-C	9.8	121
OPS13-C	9.8	112
OPS14-C	9.8	130
OPS15-C	9.8	130
OPS16-C	11.0	112
OPS17-C	12.8	116
OPS18-C	13.8	146
OPS19-C	13.8	145
OPS20-C	13.8	170
OPS21-C	19.5	180
OPS22-C	23.7	199
OPS23-C	23.7	204
OPS24-C	29.0	270
OPS25-C	29.0	270

