

Complete Dry Sprinkler System Filling Solutions



Oil-Less, Riser Mount Air Compressors for Dry Pipe & Pre-Action Sprinkler Systems

Introducing the most advanced Fire Protection Air Compressors ever built! The OL Advance Series Riser Mount Air Compressors Feature an all-new, UL 508 Listed, General Air Products Digital Pressure Switch. The OL Advance Series Air Compressors are UL 1450-VDUR Listed and specifically designed to fill dry pipe and pre-action fire sprinkler systems to supervisory pressure within 30 minutes per NFPA 13.

- UL 1450-VDUR Listed
- **Oil-Less Piston Compressor**
- UL Listed, Digital Pressure Switch
 Pre-Wired & Pre-Tested
- Fully Automatic, Direct Drive
- ASME Pressure Safety Valve
- Bubble Tight Air Check Valve
- Lifetime Technical Support





New Digital Pressure Switch: The ONLY UL Listed Digital Pressure Switch in the Fire Protection industry designed and built by the compressor manufacturer themselves. Displays Pressure Readings, Run Hours, Amps, Cycles, and is extremely easy to adjust pressure settings in the field.

| System Capacity (gal) * | | Model | Average | Motor | Voltage | Amperage (amps) | | Recommended Wire Size (gage) | | | Unit Weight |
|----------------------------|----------------------------|---------------|---------|-------|---------|--------------------|-------------|---------------------------------|------------|-------------|----------------|
| @ 40 PSI | @ 20 PSI | Number | CFM** | HP | (volts) | FLA | Start Up | 25' Run | 50' Run | 100' Run | (lbs) |
| 120 | 320 | OLRV12016AC | 1.46 | 1/6 | 115 | 3.5 | 25 | 12 | 12 | 12 | 29 |
| 120 | 320 | OLKVIZUIOAC | | | 208-230 | 1.9 | 13.3 | 12 | 12 | 12 | |
| 250 | 250 550 OLRV25033AC | 3.03 | 1/3 | 115 | 4.3 | 30.1 | 12 | 12 | 10 | 33 | |
| 250 | 550 | OLK V 25033AC | 3.03 | '/3 | 208-230 | 2.3 | 16.1 | 12 | 12 | 12 | 33 |
| 400 | 860 | OLRV40050AC | 4.85 | 1/2 | 115 | 9.4 | 65.8 | 12 | 10 | 6 | 45 |
| 400 | 000 | OLKV40050AC | | | 208-230 | 4.9 | 34.3 | 12 | 12 | 12 | |
| 500 | 995 | OLRV50075AC+ | 6.06 | 3/4 | 115 | 9.4 | 65.8 | 12 | 10 | 6 | 45 |
| | | | | | 208-230 | 4.9 | 34.3 | 12 | 12 | 12 | |
| 600 | 1250 | OLRV600100AC+ | 7.28 | 1 | 115 | 9.4 | 65.8 | 12 | 10 | 6 | 45 |
| 600 | | | | | 208-230 | 4.9 | 34.3 | 12 | 12 | 12 | |

- * System Capacity based on 30min fill at 40 PSIG and 70°F system temperature.
- ** CFM is based on the average free air delivery as the system fills from 0 to 40 PSIG.
- + Compressor has a capacity above 5.5 CFM at 10 PSIG. Air Maintenence Device required per NFPA 13.

Note: All information is subject to change without notice. Consult factory for most up-to-date product details.

Fire Protection Air Compressor Accessories

Air Maintenance Device - Part # AMD-1



The AMD-1 regulates the volume of air being delivered to the sprinkler system by the air compressor.

Per NFPA 13 - An Air Maintenance Device is required on every dry system unless the air compressor has a capacity less than 5.5 ft3/min at 10 PSI.

Motor Line Starter - Thermal Overload Protection



| SINGLE PHASE MOTOR LINE STARTERS | | | | | | | | |
|----------------------------------|------|----------|------|-------|--|--|--|--|
| | 115V | 208/230V | Size | Model | | | | |
| MAX HP | ⅓ HP | 1 HP | 00 | MG00A | | | | |
| | 1 HP | 2 HP | 0 | MGX0A | | | | |
| | 2 HP | 3 HP | 1 | MG01A | | | | |
| | 3 HP | 5 HP | 1P | MG15A | | | | |

WARNING: Cancer and Reproductive Harm - www.p65warnings.ca.gov

When Ordering a Motor Starter you must specify HP, Voltage & Phase.



Complete Dry Sprinkler System Filling Solutions

OL Advance Series - Riser Mount Fire Protection Air Compressors





