

REVISIONS				
ECO	REV	DESCRIPTION	DATE	APPROVED
0810	0	RELEASE OF DRAWING	12/19/24	TJK

LEFT TOWER

RIGHT TOWER

LEFT TOWER  
PRESSURE GAUGE

CONTROL BOX

RIGHT TOWER  
PRESSURE GAUGE

COMPRESSOR

PRESSURE  
TRANSDUCER

FILTER ASSEMBLY

PRESSURE GAUGE

1/2 NPT OUTLET

10 GALLON  
RECEIVER

16.00  
MOUNTING HOLES

DRAIN VALVE

VALVE MANIFOLD

NOTES:

1. MOUNT UNIT TO A FIRM LEVEL BASE, USING SUPPLIED VIBRATION PAD.
2. ACCEPTABLE AMBIENT TEMPERATURE RANGE IS 50° F TO 100° F.
3. CONNECT CORRECT SUPPLY VOLTAGE TO STARTER LINE TERMINALS IN CONTROL PANEL. POWER SUPPLY VOLTAGE MUST MATCH VOLTAGE ON UNITS MODEL/SERIAL NUMBER LABEL ON THE INSIDE OF THE CONTROL PANEL DOOR.
4. ALLOW CLEARANCE ON ALL SIDES OF DRY AIR PAC FOR MAINTENANCE. MINIMUM CLEARANCE BETWEEN AFTERCOOLER AND WALL IS 12" FOR AIR FLOW.
5. APPROXIMATE WEIGHT: 173 LBS, SHIPPING: 204 LBS
6. INDOOR USE ONLY

AFTERCOOLER

CHECK VALVE

9.00  
MOUNTING HOLES



APPROVALS	DATE	TITLE:
DRAWN DL	1/9/2024	GA DAP 500
CHECKED TK	1/9/2024	
SCALE NONE	SIZE B	DWG. NO. <b>G-223175</b>
SHEET 1 OF 1		REV <b>0</b>

UNLESS OTHERWISE SPECIFIED,  
DIMENSIONS ARE IN INCHES.  
TOLERANCES ARE:  
FRACTIONS DECIMALS ANGLES  
±X .XX±X ±X°

THIS DRAWING AND ALL OF ITS CONTENTS ARE THE SOLE PROPERTY OF GENERAL AIR PRODUCTS, INC. DETAILS MAY CHANGE WITHOUT NOTICE. THE CONTENTS OF THIS DRAWING MAY NOT BE REPRODUCED OR INCORPORATED IN WHOLE OR IN PART IN ANY EQUIPMENT, NOR THE MANUFACTURE OF ANY PARTS, WITHOUT WRITTEN CONSENT OF GENERAL AIR PRODUCTS, INCORPORATED.